

/ ALEX Single-String Solution



VOLTAGE®
ALEX

Key Features


- Aluminum home run extensions that run from multi-string harnesses or modules to the end of the row.
- Customized design to accommodate site layouts.
- Significantly lowers overall budget price of the project.
- Friction welded CU-AL transitional joints used to eliminate increased oxidation caused by the surface contact of dissimilar metals.
- IP68 overmold protects the components from the environment and any occurrences that could damage the transitional joint.

Construction

- Joint: 35kV-rated with anti-oxidation and anti-corrosion joint compound.
- Mold: Weather resistant outdoor rating per UL 746C and UL 94 Flame-retardant 90°C rated.
- All major connectors available per specific design requirements.

Standards

- Certified to UL Std. 9703
- Certified to CAN/CSA Std. C22.2 #182.5 Photovoltaic Connectors
- Certified to CAN/CSA Std. C22.2 #271 Photovoltaic Cables
- Certified to CAN/CSA Std. C22.2 #198.2 Sealed Wire Connector Systems



Technical Data

Voltage Rating	2000V DC
2kV CU Conductor Isc. Range	12AWG (35A) – 6AWG (86A)
2kV AL Conductor Isc. Range	6AWG (70A) – 1AWG (86A)
Operating Temperature	-40°C ~ 90°C
Max Ambient Temperature	50°C
Connectors, Overmolds, In-line Fuses	IP68 Rated (1m/24hrs)
Dustcaps	IP65 Rated (Tested with 12.5 L/min water jet from 2.5-3m distance for 3 minutes)

Conductor Size

Copper	Aluminum
12	6
10	6
8	6
6	6
10	4
8	4
6	4
10	2
8	2
6	2
8	1
6	1





Website



LinkedIn



TEL:
(919) 391-9405



Website:
voltageenergy.com



Email:
sales@voltageenergy.com



Address:
1450 Raleigh Road, Suite 208 Chapel Hill, NC 27517 USA

The Voltage name and associated logos, in addition to other trademarks used herein, are owned exclusively by Voltage, LLC, and are registered with the U.S. Patent and Trademark Office. All rights reserved.